

Flap Wheels



Flap Wheels are designed with the circular arrangement of individual fabric abrasive cloth around a reinforced wood which is suitable for use on threaded shaft. It allows for easy fitting and removing from stationary or handheld tool. The flap design allows the wheel to contour around the work piece and smooth the surface.

Finishing for stainless steel, aluminum, plastics, fibre glass, rubber, stone, alloys alloyed steel. Use on flat, concave and convex surfaces. Internal and external surfaces or sides, irregular shapes. For removing and cleaning of welding seams.

Our flap wheels are made from Aluminum Oxide(AO) cloth(X-weight)

Mounted flap wheels comes in 6mm or 3mm shanks for use with hand tools.

Specifications

| Grits (#) | Dimensions (inches, mm) |
|---|--|
| 40, 60, 80, 100, 120, 150, 180, 220, 240, 320, 400, 600 | 6"x1", 6"x2", 7"x1" |
| 60,80,120 | 10x15x3mm, 15x15x3mm, 20x30x3mm, 25x10x3mm, 30x10x3mm |
| 60, 80, 120, 150, 180, 240, 320 | 20x25x6mm, 25x25x6mm, 30x25x6mm, 40x25x6mm, 50x25x6mm, |
| 60,80 | 60x25x6mm, 80x25x6mm |

Everbrite Abrasive Pte Ltd

Blk 5026, Ang Mo Kio Industrial Park 2, #01-91, Singapore 569529

Tel: +65 6484 7582, Fax: +65 6484 9570

Web: <http://everbriteabrasive.net> Email: sales@everbriteabrasive.net